



# RJ-4000

## 4" Mobile Label/Receipt Printer Series

The tough 4" printing solution to support workers on the move



# RJ-4000 Series

Rugged mobile printing, whatever the conditions

## RELIABLE

Direct thermal print suitable for a wide range of environmental conditions

## DURABLE

IP54 rating and drop test – designed to withstand even the harshest conditions

## EASY TO USE

USB, Serial, Bluetooth and wireless interface options

## MOBILE

Compact, lightweight and rugged for mobile workers



## EASY TO INTEGRATE





Simple integration into existing applications with free software development kit (SDK)\*.

## CUSTOMISABLE

Power options include rechargeable batteries, AC adaptor or vehicle power kits

\*Available from: <https://online.brother.co.uk/developer>

## Step 1. Choose your printer

|   | RJ-4030 | RJ-4040 |
|---|---------|---------|
| 203dpi print resolution   | ✓       | ✓       |
| IP54 Certification  | ✓       | ✓       |
| 6ft drop protection   | ✓       | ✓       |
| 5 ips print speed   | ✓       | ✓       |
|    | ✓       | ✓       |
|    | ✓       |         |
|   |         | ✓       |

# Mobile printers for fast, reliable printing on the move

Our RJ-4000 series mobile printers are fast, compact and very rugged, perfect for busy mobile workers out in the field. They allow you to print up to 4" receipts, quotes, tickets, invoices and labels on demand, improving efficiency, productivity and customer service.

## WAREHOUSING

- ✓ Shipping labels
- ✓ Inventory labels
- ✓ Pallet labels

## LOGISTICS/ DELIVERIES

- ✓ Delivery notes
- ✓ Delivery receipts

## FIELD SALES

- ✓ Sales quotations
- ✓ Sales invoices & contracts
- ✓ Sales receipt

## EMERGENCY SERVICES

- ✓ Ticketing
- ✓ Penalty notices
- ✓ Patient treatment information

## FIELD SERVICE

- ✓ Service reports
- ✓ Safety reports
- ✓ Appliance certifications



## Step 2. Choose your Accessories

| Power Options   |   |   |   |   |
|---|---|---|---|---|
| PA-BT-4000LI  | PA-AD-600EU   | PA-CD-600UK   | PA-CD-600CG 12V   | PA-CD-600WR 12V   |
| Li-ion rechargeable battery   | AC adapter (EU)   | AC adapter (UK)   | 12V car adapter (cigarette socket)  | 12V car adapter (permanently wired)   |
|  |  |  |  |  |

| Additional Options  |   |   |   | Label/Paper Options   |   |
|---|---|---|---|---|---|
| PA-MCR-4000   | PA-CM-4000  | PA-WC-4000  | PA-SS-4000  | RD-M01E5  | RD-M03E1  |
| Magnetic card reader  | Car mounting kit  | Weather case  | Shoulder strap  | 4" wide paper rolls (receipt)   | 4" wide label rolls   |
|  |  |  |  |  |  |

# Specifications

| PRINTING                        | RJ-4030  | RJ-4040  |
|---------------------------------|--|--|
| Print resolution                | 203dpi   |  |
| Print technology                | Direct thermal   |  |
| Print speed                     | Maximum 5ips (inches per second) or 127mm/second (under Brother standard environment *1)   |  |
| Paper feed method               | Roll feed  |  |
| Print width                     | Maximum 104mm (4.09 inches)  |  |
| Print length                    | Maximum 3m (118.11 inches)   |  |
| No. of pages per battery charge | Rechargeable Li-ion Battery: approximately 2000 labels - continuously printing. (under Brother standard environment *1)                        |  |
| Barcode                         | Yes  |  |
| <b>Interfaces</b>               |  |  |
| USB                             | Standard   |  |
| Serial                          | Standard   |  |
| Bluetooth (Ver. 2.0 + EDR)      | Standard   | N/A  |
| WiFi (802.11 b/g/n)             | N/A  | Standard   |
| <b>Memory</b>                   |  |  |
| Memory size (RAM/Flash)         | 32MB / 16MB  |  |
| <b>General</b>                  |  |  |
| Dimensions                      | 6.38" x 6.93" x 3.03" (162mm x 176mm x 77mm)   |  |
| Weight excl battery & paper     | 610g/1.35lb (approx)   |  |
| Battery                         | Rechargeable, Li-ion 14.4V   |  |
| AC adapter                      | AC adapter 12 V (optional accessory)   |  |
| Car adapter                     | Cigarette lighter plug or permanently wired (optional accessories)   |  |
| Operating system support        | Windows XP, Windows Vista, Windows 7, Windows 10   | Windows XP, Windows Vista, Windows 7, Windows 10, Windows Server 2003, Windows Server 2008/2008 R2 |
| Mobile OS                       | Windows CE 5.0 & later, Windows Mobile 5 & later, Android 2.2 & later  | Windows CE 5.0 & later, Windows Mobile 5 & later, Android 2.2 & later, iOS 5                       |
| Emulation                       | ZPL II® Compatible   |  |
| Supported Command               | P-touch Template 2.0, Raster, ESC/P  |  |
| Roll width (Max/Min)            | 118mm (4.64") / 51mm (2.0")  |  |
| Maximum roll diameter           | 58mm (2.28")   |  |
| <b>Environmental</b>            |  |  |
| Temperature                     | 0C to +40C (During Operation) -20C to +60C (During Storage)  |  |
| Humidity                        | 20%-80% (No Condensation)  |  |
| Drop protection                 | 1.8m (6ft)   |  |
| Sealing certification           | IP54   |  |
| <b>Contents</b>                 |  |  |
|                                 | RJ Printer (RJ4030 or RJ4040), Belt clip, Quick Set up Guide, CD-ROM (printer driver and user manual) includes Barcode & Label Design Software |  |

\* 1 Figures quoted depend on operating environment. "Brother standard environment" is based on connectivity via USB with fully charged new battery at 23 degrees C. (7% coverage 4X6 inches.)

Contact:

## Brother UK

Audenshaw, Manchester M34 5JD  
 Tel: 0333 777 4444 Fax:+44 (0)161 931 2218  
 Web: [www.brother.co.uk](http://www.brother.co.uk)

All specifications correct at time of printing. Brother is a registered trademark of Brother Industries Ltd. Brand product names are registered trademarks or trademarks of their respective companies.

**brother**  
 at your side