



## 4-Inch Direct Thermal Desktop Label Printers Data Sheet

TD-4215D / TD-4425DN / TD-4525DN / TD-4455DNWB / TD-4555DNWB/  
TD-4425DNFC / TD-4555DNWBFC

# 4" Professional Direct Thermal Printer

Brother's range of TD professional label printers allows you to print high quality labels on demand, whatever the requirement.

Printing labels up to 4 inches in width, using direct thermal print technology, they fit the requirements of a large range of market applications.



## Key Features

- Fast print speeds of up to 203mm/sec (8ips)
- Direct thermal printing on a range of media including linerless<sup>3</sup>
- Auto media configuration for easy setup
- Ready to integrate with iOS & Android apps
- USB-C, USB Host and Serial connectivity as standard<sup>1</sup>

Wide feeding slot with window for oversized media

User replaceable print head and platen roller (optional)

LCD display with Real Time Clock<sup>1</sup>

Bluetooth interface<sup>1</sup>

Wireless LAN supporting 2.4GHz and 5GHz bands<sup>1</sup>

Pre-installed cutter with label taken sensor (Linerless models)<sup>3</sup>

## General

<b>Carton contents</b>	AC adaptor + power cord USB cable Documentation Roll Holder
<b>Language support</b>	Dansk, Deutsch, English, Español, Français, Italian, Nederlands, Norsk, Português, Suomi, Svenska

## Dimensions & Weights

<b>Without carton</b>	180(w) x 224(d) x 155(h)   2.08Kg 180(w) x 224(d) x 155(h)   2.12Kg <sup>^</sup> 180(w) x 255(d) x 155(h) mm   2.49Kg <sup>3</sup>
-----------------------	--

## Built In Features

<b>Printing Method</b>	Direct Thermal
<b>Minimum print length</b>	Continuous: 6.4mm, Peeler: 17mm, Cutter: 20mm, Tear: 18mm (Cutter mode only for Linerless models) <sup>3</sup>
<b>Maximum print length</b>	3000mm
<b>Minimum media width</b>	19mm 39mm (Linerless models) <sup>3</sup>
<b>Maximum media width</b>	106mm (Linerless models) <sup>3</sup> 118mm
<b>Maximum roll diameter</b>	102mm (Linerless models) <sup>3</sup> 127mm
<b>Minimum roll core diameter</b>	12.7mm 25.4mm (Linerless models) <sup>3</sup>

<b>Interfaces</b>	USB Ver.2.0 (Full Speed) (Type C) USB Host <sup>^</sup> Serial RS232C (DB9 male) Bluetooth Dual Mode(Classic + LE) (SPP, OPP, HCRP, GATT/MFi) <sup>1</sup> Wireless LAN 802.11a/b/g/n supporting 2.4GHz & 5GHz (supporting AirPrint <sup>®</sup> from iOS <sup>®</sup> devices) <sup>1</sup> Wired LAN 10/100BASE-TX <sup>2</sup>
-------------------	--

<b>Operating system support</b>	Microsoft <sup>®</sup> Windows <sup>®</sup> 10 / Windows <sup>®</sup> 11 Microsoft <sup>®</sup> Windows <sup>®</sup> Server 2016 / Server 2019 / Server 2022 / Server 2025 (TD-4425DN, TD-4525DN, TD-4455DNWB, TD-4555DNWB, TD-4425DNFC, TD-4555DNWBFC)  Linux
---------------------------------	---

<b>Mobile OS Support</b>	Android 8 or later iOS <sup>®</sup> 15 or later (TD-4425DN, TD-4525DN, TD-4455DNWB, TD-4555DNWB, TD-4425DNFC, TD-4555DNWBFC) Requires 3 <sup>rd</sup> party app development using Brother SDK, further information available at <a href="https://www.brother.eu/en/developer">https://www.brother.eu/en/developer</a>
--------------------------	---

<b>Software</b>	<b>P-touch Editor:</b> barcode label design software  <b>Mobile Deploy App:</b> remote printer configuration <sup>^</sup>  <b>Brother Font Manager:</b> font download tool (Windows <sup>®</sup> only via USB)  <b>BRConfiguration Tool:</b> device configuration software (Windows <sup>®</sup> only)
-----------------	--

<b>Printer commands</b>	Raster, ESC/P, P-touch Template, ZPL2, EPL2, DPL & CPCL emulations (for additional command support contact your local Brother office)
-------------------------	--

<b>Internal fonts &amp; sizes</b>	<b>&lt;ESC/P&gt;</b> Bitmap font: LetterGothicBold (16,24,32,48dot), Helsinki (16,24,32,48dot), Brussels (24,32,48dot), Brougham (24,32,48dot), San Diego (24,32,48dot), Gothic (16,24,32dot) Outline font: LetterGothic, Helsinki, Brussels, Gothic (1 – 400dots) <b>&lt;P-touch Template&gt;</b> Outline font: LetterGothic, Helsinki, Brussels, Gothic (1 – 400dots)  Downloadable font support* via Font Manager software
-----------------------------------	---

<b>Internal Barcode</b>	<b>Linear:</b> CODE 39, ITF(I-2/5), EAN-8(JAN8), EAN-13(JAN13), UPC-A, UPC-E, CODABAR (NW-7), CODE 128, GS1-128(UCC/EAN 128), GS1 Databar(Omni, Truncated, Stacked, Stacked Omni, Limited, Expanded, Expanded Stacked) CODE93, POSTNET, UPC/EAN EXTENSION, MSI, Intelligent Mail Barcode  <b>2-dimensional:</b> QR Code (model 1, model 2, micro QR), Maxicode, PDF417 (Standard, Truncate, MicroPDF417) Data Matrix (ECC200 Square, ECC200 Rectangular), Aztec
-------------------------	--

## Environmental

<b>Operating Temperature</b>	5°C to 40°C
<b>Operating Humidity</b>	20% to 85% non-condensing
<b>Storage Temperature</b>	-20°C to 60° C
<b>Storage Humidity</b>	10% to 95% non-condensing

## Supplies

<b>Receipts<sup>6</sup></b>	BDL-7J000102-058: 101.6mm x 32.2m BDL-7J000076-066: 76mm x 42m BDL-7J000058-102: 58mm x 101.6m BDL-7J000058-040: 58mm x 13.8m
<b>Labels<sup>6</sup></b>	BDE-1J152102-058: 85 labels - 102mm x 152mm BDE-1J000102-102: Continuous labels - 102mm x 58m BDE-1J050102-102: 1,050 labels - 102mm x 50mm BDE-1J152102-102: 350 labels - 102mm x 152mm BDE-1J026076-102: 1,900 labels - 76mm x 26mm BDE-1J044076-066: 400 Labels - 76mm x 44mm BDE-1J026051-102: 1,900 labels - 51mm x 26mm BDE-1J026051-060: 500 Labels - 51mm x 26mm
<b>Linerless Labels<sup>3</sup></b>	BFA-274058-080 Linerless Label, 58mm x 51.8m BFA-274106-080 Linerless Label, 106mm x 51.8m BFA-274080-080 Linerless Label, 80mm x 51.8m BFA-274039-102 Linerless Label, 39mm x 82.3m BDA-274058-080 Linerless Label, 58mm x 51.8m BDA-255058-102 Linerless Label, 58mm x 114m

## Optional Accessories (User Option)

<b>Label Peeler</b>	PA-LP-002 <sup>6</sup>
<b>Cutter</b>	PA-CU-001 <sup>6</sup>
<b>Linerless cutter</b>	PA-LCU-002 <sup>3</sup>
<b>Thermal print head</b>	203dpi: PA-HU2-001 300dpi: PA-HU3-001
<b>Platen Roller</b>	203dpi: PA-PR2-001 <sup>6</sup> 300dpi: PA-PR3-001 <sup>6</sup>
<b>Linerless Platen Roller</b>	203dpi: PA-LPR2-002 <sup>4</sup> 300dpi: PA-LPR3-002 <sup>5</sup>
<b>Healthcare power adapter (IEC-60601)</b>	PA-AD-006EU PA-AD-006UK

<sup>1</sup>TD-4455DNWB / TD-4555DNWB / TD-4555DNWBFC only

<sup>2</sup>TD-4425DN/TD-4525DN/TD-4455DNWB/TD-4555DNWB/  
TD-4425DNFC/TD-4555DNWBFC only

<sup>3</sup>TD-4425DNFC / TD-4555DNWBFC only (Linerless models)

<sup>4</sup>TD-4425DNFC only (Linerless model)

<sup>5</sup>TD-4555DNWBFC only (Linerless model)

<sup>6</sup>Not compatible with TD-4425DNFC / TD-4555DNWBFC (Linerless models)

<sup>^</sup>TD-4455DNWB/TD-4555DNWB only

\*Font Licensee permissions are required

## Model Comparison

	TD-4215D	TD-4425DN / TD-4425DNFC	TD-4525DN	TD-4455DNWB	TD-4555DNWB / TD-4555DNWBFC
<b>Maximum print width</b>	104mm	104mm	108mm	108mm	108mm
<b>Print resolution</b>	203dpi	203dpi	300dpi	203dpi	300dpi
<b>Printing speed</b>	5ips (127mm/sec)	8ips (203mm/sec)	6ips (152mm/sec)	8ips (203mm/sec)	6ips (152mm/sec)
<b>USB-C / USB Host</b>	Yes / No	Yes / No	Yes / No	Yes / Yes	Yes / Yes
<b>Serial</b>	Yes	Yes	Yes	Yes	Yes
<b>Wired LAN</b>	-	Yes	Yes	Yes	Yes
<b>Bluetooth</b>	-	-	-	Yes	Yes
<b>Wi-Fi</b>	-	-	-	Yes	Yes
<b>LCD (incl. Real Time Clock)</b>	-	-	-	Yes	Yes

All specifications are correct at the time of printing and are subject to change without notice. Brother and the brother logo are both trademarks of Brother Industries, Ltd., registered in Japan and certain other countries. Any trade names, logos and product names of other companies appearing are trade names or trademarks of those respective companies.

BIE Product Planning: Last updated 17/11/2025