

COMPACT, SPEEDY A4 COLOUR MULTIFUNCTION PRINTERS FOR ESSENTIAL PRINTING AND SCANNING.

Create high quality documents with printers designed to fit seamlessly into a variety of work environments.

i-SENSYS MF660 Series



HIGH-QUALITY PRINTING

Produce high-quality output from toners with a wide range of colours and achieve bright, vibrant prints with excellent reproduction of both light and dark tones.

IMPROVE SUSTAINABILITY EFFORTS

Increase your sustainability efforts by opting for devices that increase use of recycled plastic. The light weight of printers also means fewer emissions during transport.

GREATER PRODUCTIVITY

Boost collaboration and productivity with fast print and scan speeds. Easily scan small-sized documents, including cheques and receipts, to cutdown on manual entry and paper storage.

SMOOTH USER EXPERIENCE

Use the intuitive UI to easily carry out a range of print and scan tasks and quickly reach relevant parts of the online manual via a QR code. Save time with the Master Setup which automatically downloads and installs software.

360-DEGREE SECURITY

A Security Settings Navigator recommends appropriate settings to protect against security leaks and cyber threats.

Canon

TECHNICAL SPECIFICATIONS

i-SENSYS MF660 Series

| MAIN UNIT | |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Machine type | Colour Laser All-In-One |
| Available functions | Print, Copy, Scan and Fax |
| PRINTER | |
| Print speed | Single sided : Up to 25 ppm (A4) Up to 45.3 ppm(A5-Landscape) Double sided : Up to 15 ipm (A4) |
| Printing method | Colour laser beam printing |
| Print resolution | Up to 1200 x 1200 dpi |
| Warm-up time | Approx. 13 seconds or less from power on |
| First Print Out Time | Colour approx.: 10.93 seconds or less Mono approx.: 10.90 seconds or less |
| Printer languages | i-SENSYS MF664Cdw : UFR II, PCL 5c ² , PCL6 i-SENSYS MF667Cdw : UFR II, PCL 5c ² , PCL6, Adobe® PostScript ³ |
| Fonts | i-SENSYS MF664Cdw : 45 PCL fonts i-SENSYS MF667Cdw : 93 PCL fonts, 136 PostScript fonts |
| Print margins | 5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope) |
| Toner saver mode | Yes |
| Advanced printing features | i-SENSYS MF664Cdw: Encrypted Secure Print Secure Print Print from USB memory key (JPEG/TIFF/PDF) Print from Cloud (Dropbox, GoogleDrive, OneDrive) (PDF/JPEG) Microsoft Universal Print support iOS: AirPrint, Canon PRINT app Android; Mopria certified, Canon Print Service Plug- in, Canon PRINT app, IPP everywhere |
| | i-SENSYS MF667Cdw: Encrypted Secure Print Secure Print Print from USB memory key (JPEG/TIFF/PDF) Print from Cloud (Dropbox, GoogleDrive, OneDrive) (PDF/JPEG) Microsoft Universal Print support Barcode Print ³ iOS: AirPrint, Canon PRINT app Android; Mopria certified, Canon Print Service Plug- in, Canon PRINT app, IPP everywhere |
| COPIER | |
| Copy speed | Single sided (A4): Up to 25 ppm Double sided (A4): Up to 15 ipm |
| First Copy Output Time (FCOT) | ADF (A4): Colour Approx. 10.6 seconds or less Mono Approx. 10.5 seconds or less Platen (A4): Colour Approx. 11.2 seconds or less Mono Approx. 11.0 seconds or less |
| Copy resolution | Up to 600 x 600 dpi |
| Copy modes | Text/Photo/Map (Default),Text/Photo/Map (quality), Printed Image, Text |
| Double sided copying | 2-sided to 2-sided (Automatic) |
| Multiple copy | Up to 999 copies |
| Reduction / Enlargement | 25-400% in 1% increments |
| Other features | Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Two-sided Original, Sort, N on 1, Sharpness, Erase Frame, Copy ID Card, Copy Passport, Color Mode, Reserved copy |

| SCANNER | |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type | Colour |
| Scan resolution | Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi |
| Scan speed | i-SENSYS MF664Cdw: Single sided mono: 50ipm (300x300dpi) Single sided colour: 40ipm (300x300dpi) Single sided mono: 40ipm (300x600dpi) Single sided colour: 20ipm (300x600dpi) i-SENSYS MF667Cdw: Single sided mono: 50ipm (300x300dpi) Single sided colour: 40ipm (300x300dpi) Double sided mono: 100ipm (300x300dpi) Double sided colour: 80ipm (300x300dpi) Single sided mono: 40ipm (300x600dpi) Single sided colour: 20ipm (300x600dpi) Double sided mono: 80ipm (300x600dpi) Double sided colour: 40ipm (300x600dpi) |
| Colour scanning depth | 24 bit/24 bit (input/output) |
| Greyscales | 256 levels |
| Compatibility | TWAIN , WIA, ICA |
| Max. scan width | 216mm |
| Scan to E-mail | i-SENSYS MF664Cdw: TIFF/JPEG/PDF/Compact PDF/Searchable PDF / PDF/A-1b |
| Scan to PC | i-SENSYS MF667Cdw: TIFF/JPEG/PDF/Compact PDF/Searchable PDF/ Encrypted PDF4/PDF (Digital signature) ⁴ / PDF/A-1b |
| Scan to Cloud ¹ | TIFF/JPEG/PDF/PNG ⁵ |
| iFAX | i-SENSYS MF667Cdw: ITU-T.37 |
| FAX (i-SENSYS MF667CDW ONLY) | |
| Modem speed | 33.6 Kbps (Up to 3 seconds/page ⁶) |
| Receive mode | Fax only, Fax/Tel Auto Switch, Answer Mode, Manual |
| Fax resolution | Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi |
| FAX memory | Up to 512 pages ⁶ |
| Speed dials | Up to 281dials |
| Group dials/destinations | Max. 299 dials / Max. 299 destinations |
| Sequential broadcast | Max. 310 destinations |
| Memory backup | Permanent fax memory backup (Backup with flash memory) |
| Double sided faxing | Yes (Transmit and Receive) |
| Other features | Sender's Name (TTI), Direct Send, Preview, TX Report, Sequential Broadcasting |
| MEDIA HANDLING | |
| Scanner type | i-SENSYS MF664Cdw : Platen, ADF i-SENSYS MF667Cdw : Platen, 2-sided ADF (single pass) |
| Paper input (Standard) | 250-sheet cassette 1-sheet manual feed slot 50-sheet ADF |
| Maximum paper input capacity | 251 sheets |
| Paper output | 100-sheet |

TECHNICAL SPECIFICATIONS

i-SENSYS MF660 Series

| | |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Media types | Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Label, Post card, Envelope |
| Media sizes | Cassette : A4, A5, A5 (Landscape), B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Indexcard, Envelop (COM10, DL, C5, Monarch), Custom sizes: Min. 76.2 x 127 mm Max. 216 x 355.6 mm. Multi-purpose tray: A4, A5, A5 (Landscape), B5,A6, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Post card, Indexcard, Envelope (COM10, DL, C5, Monarch), Custom sizes: Min 76.2 x 127 mm Max. 216 x 355.6 mm. ADF: A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 48 x 85.0 mm Max 216.0 x 355.6 mm |
| Media weights | Cassette: 60 to 163 g/m ² (Up to 200 g/m ² with Coated paper) Multi-purpose tray: 60 to 163 g/m ² (Up to 200 g/m ² with Coated paper) ADF: 50 to 105 g/m ² |
| Double sided printing | Automatic Cassette: A4, B5, Legal, Letter, Executive, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K Custom size - Min. 182 x 257 mm Max. 216.0 x 355.6 mm 60 to 200 g/m ² |
| INTERFACE & SOFTWARE | |
| Interface type | USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802.11b/g/n, Wireless Direct Connection |
| Operating System compatibility | Windows® 11 / Windows® 10 / Server® 2025 / Server® 2022 / Server® 2019 / Server® 2016 Mac OS X version 10.15 & up Linux ⁷ |
| Network Protocol | Print: TCP/IP (LPD/Port9100/IPP/IPPS/WSD) Scan: Push Scan: File: FTP (TCP/IP), SMB3.1.1 (TCP/IP) E-mail/I-Fax: SMTP (send), POP3 (receive) Pull Scan: TCP/IP Management: SNMPv1, SNMPv3 (IPv4,IPv6) Security: TLS1.3, IPSec, IP address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPSP) Security (wireless): Infrastructure Mode: WPA-PSK(AES), WPA2-PSK(AES), WPA3-SAE (AES), WPA-EAP(AES), WPA2-EAP(AES), WPA3-EAP(AES) Access Point Mode: WPA2-PSK(AES), WPA3-SAE (AES) |

| | |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Software and printer management | MF Scan Utility, Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices Cooperating with External Security Audit System (Security Information and Event Management) eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Application Library |
| GENERAL FEATURES | |
| Processor Speed | 1200MHz |
| Memory | 1GB |
| Storage | 4GB |
| Control panel | 12.7 cm LCD Colour Touch Screen |
| Dimensions with trays (W x D x H) | 425 mm x 461 mm x 397 mm |
| Installation space (W x D x H) | 701 mm x 1,020 mm x 785 mm |
| Weight | Approx. 20.8 Kg |
| Operating environment | Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) |
| Power Source | 220-240V(±10%) 50/60Hz (±2Hz) |
| Power Consumption | Maximum: Approx. 980 W Active printing: Approx. 580W Standby: Approx. 12.0 W Sleep mode: Approx. 1.0 W Typical Electricity Consumption (TEC): 0.23 kWh/week ¹⁾ For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For-Work/Lot26/index.aspx |
| Noise Levels | Sound Pressure ⁸⁾ : Active: Simplex 53 dB / Duplex 52 dB Standby: Inaudible Sound Power ⁹⁾ : Active: Simplex 67 dB or less (BW) / 66 dB or less (CL) Duplex 66 dB or less Standby: Inaudible |
| CONSUMABLES | |
| Cartridges | Cartridge 075 Black (1,400 pages ⁹⁾ ¹⁰ Cartridge 075H Black (3,500 pages ⁹⁾ ¹⁰ Cartridge 075 Cyan (1,300 pages ⁹⁾ ¹⁰ Cartridge 075H Cyan (2,500 pages ⁹⁾ ¹⁰ Cartridge 075 Magenta (1,300 pages ⁹⁾ ¹⁰ Cartridge 075H Magenta (2,500 pages ⁹⁾ ¹⁰ Cartridge 075 Yellow (1,300 pages ⁹⁾ ¹⁰ Cartridge 075H Yellow (2,500 pages ⁹⁾ ¹⁰ |
| ACCESSORIES/ OPTIONS | |
| Items | i-SENSYS MF667Cdw: TEL 6 Kit Long Cord (Telephone handset) Barcode Printing Kit-E1E Send PDF Security Feature Set-E1 |

TECHNICAL SPECIFICATIONS

i-SENSYS MF660 Series

Notes:

1. Subscription to a third party cloud service is required, and subject to their party terms and conditions.
2. Commands supported only. Third party driver or direct printing from application required.
3. Accessory - Barcode Printing Kit-E1E - is required
4. Accessory - Send PDF Security Feature Set-E1 is required
5. Scan by MF Scan Utility or Canon PRINT
6. Based on ITU-T Standard Chart No. 1
7. Web distribution only. Linux support printing only.
8. Declared noise emission in accordance with ISO 7779.
9. Based on ISO/IEC 19798
10. Printer ships with Black: 700 pages, C/M/Y: 500 pages starter cartridges
11. As per US ENERGY STAR® version 3.2.



Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Telephone No: 01 2052400
Facsimile No: 01 2052525
canon.ie

Canon (UK) Ltd
The Bower
4 Roundwood Avenue
Stockley Park
Uxbridge
UB11 1AF

Canon Inc.
Canon.com
Canon Europe
canon-europe.com
English Edition
© Canon Europa N.V. 2025