



Models may vary from the image shown

Thanks to its compact size the waterproof AK-C4412 Medical Keyboard is perfect for areas with limited spaces. It comes with a high-responsive touchpad that allows for excellent cursor control as you know it from any PC mice. The disinfection capablities makes it a perfect fit in hospitals and at maederal practitioners, microbiological laboratories as well as industrial environments. The silicone key membrane protects the key pad of the AK-C4412 against the ingress of dirt and fluids and promotes a thorough wipe disinfection.

The ulta-flat key profile and the entirely closed surface is an effective barrier against cross contamination and the spread of germs. Equipped with the seamless closed membrane, the AK-C4412 corresponds to the requirements of the protection class IP68. The "CleanFunction" makes it possible to turn off the key pad while cleaning ("FN" + "Clean on/off").

FUNCTION AND PERFORMANCE

- Compact-sized Medical Keyboard for areas with strict cleaning protocols
- Waterproof, gap-free design to protect the keyboard from liquids, dirt and debris

- Ultra-flat key profile ensures maximum wipe disinfection while maintaining optimal haptics for an excellent typing experience
- Approved for wipe disinfection according to VAH Guideline (German Association of Applied Hygiene)
- Fully sealed with IP68 rating
- High-responsive touchpad allows for precise cursor control
- CleanFunction enables the keys to be switched off during cleaning
- Four 75 mm threaded holes for VESA mount

TECHNICAL DATA

Weight main product:	570 g
Dimensions product without packaging:	364 mm x 139 mm x 17 mm
Weight of product incl. packaging:	690 g
Dimensions product incl. packaging:	380 mm x 205 mm x 25 mm
Content of master carton (pieces):	20
Weight of master carton incl. content:	15,000 g
Dimensions master carton:	400 mm x 273 mm x 447 mm
Storage temperature:	-20 °C - 60 °C
Working temperature:	0 °C - 50 °C
System Requirements-Hardware:	USB-A
Operating system:	All operating systems that support USB keyboard interface
Scope of delivery:	<ul style="list-style-type: none"> • Keyboard • Manual
Reliability:	MTBF 90: > 10 Mio.
Switching characteristics:	tactile
Max. current consumption (mA) of keyboard:	31 mA

Actuating force (cN):	60 cN
Total Key Travel:	2,5 mm
Key labeling:	Silk screen printing on silicon membrane
Number of keys:	78
Special key functions:	<ul style="list-style-type: none">• FN Key• CleanFunction

Status LEDs:	in housing
Key technology:	Scissor
Keycap material:	ABS
Protection class:	IP 68

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products. Properties are not guaranteed.

SKU / EAN / UPC	Protection class	Colour	Layout
AK-C4412F-GUS-W/GE EAN 7061117414480 UPC	IP 68	white	DE (Germany)
AK-C4412F-GUS-W/NOR EAN 7061114190295 UPC	IP 68	white	PN (PanNordic)
AK-C4412F-GUS-W/UK EAN 7061117036156 UPC	IP 68	white	GB (United Kingdom)

Please contact your local CHERRY service and support teams or your CHERRY sales partners for versions available in your country.