

> PRINT > COPY > SCAN > FAX

ECOSYS M8130cidn

COLOUR MULTIFUNCTIONAL FOR A4/A3 FORMAT

RICH FEATURE. AFFORDABLE PRICE.



- > Up to 30/15 pages A4/A3 per minute
- > Highly productive, professional print, copy, colour scan and fax functionality
- > Minimum installation and operation requirements

- > Easy to use full colour touch panel with wizard-style navigation
- > Low power consumption saves energy
- > Long-life components provide unprecedented efficiency and reliability
- > HyPAS[™] solution platform enables powerful customisations



COSYS ECOSYS stands for ECOlogy, ECOnomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you and the environment less.

GENERAL

Technology: KYOCERA ECOSYS, Laser, Colour, HyPAS™ solution platform

Operation praction: 777.8 mm (7 inch) full-colour touch panel display, speaker for job notification

Type: Desktop

Engine speed: Up to 30/15 pages A4/A3 per minute in colour and b/w. Duplex print speed: 26 page per minute, A4, Duplex copy speed: 26 page per minute, A4 Resolution: 1200 x 1200 dpi (print), 600 x 600 dpi

Warm-up time: Approx. 30 seconds or less
Time to first print: Approx. 6.5 seconds or less in b/w,
8.3 seconds or less in colour

Time to first copy: Approx. 7.4 seconds or less in b/w (DP), Approx. 9.3 seconds or less in colour (DP), Approx. 6.5 seconds or less in b/w (platen cover), Approx. 8.3 seconds

seconds or less in b/W (platen cover), Approx. 8.3 seconds or less in colour (platen cover)

CPU: ARM Cortex-A9 Dual core 1.2GHz

Memory: Standard 1.5 GB, Max. 3GB + 128GB SSD

Standard interface: USB 2.0 (Hi-Speed), 2 x USB Host

Interface, Gigabit Ethernet (10BaseT/100BaseTX/
1000BaseT), optional Wi-Fi (IEEE 802.11b/g/n), 2 eKUIO

slots, for optional fax system Slot for optional SD Card NFC tax

slots, for optional internal prints server or SSD nard discs and for optional fax system, Slot for optional SD Card, NFC tag Integrated accounting: 100 department codes Dimensions (WxDxH):

590 x 590 x 753 mm (with standard Document Processor)
Weight: Approx. 79 kg (with standard Document Processor)
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption
Printing: RSO W

Printing: 580 W Copying: 580 W Low power mode: 40 W Ready mode: 80 W

Noise (sound pressure level: ISO 7779/ISO 9296)
Copying/Printing in b/w: 53 dB (A)

Copying/Printing in colour: 54 dB (A)

Safety standards: TÜV/GS, CE
This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity:

100-sheet multi-purpose tray, 60–256 g/m², A3, A4, A5, A6, B5, Ledger, Letter, Legal, Folio, Custom (98 x 148 to 297 x 432 mm), 500-sheet Standard universal paper cassette, 60–256 g/m², A3, A4, A5, B5, Ledger, Letter, Legal, Folio, Max. input capacity with options: 1,600 sheets

Duplex unit: Duplex as standard supports 60–220 g/m²
Standard reversing document processor: 60–320 g/m²
Standard reversing document processor: 60–320 g/m² Standard reversing document processor: 50-sheets, A3, A4, A5, B5, Letter, Legal, Custom (140 x 182 to 297 x 432 mm), Simplex scan 45—160 g/m², Duplex scan 50—120 g/m² Output capacity: Max. 280 sheets; 250 sheets face-down (Main Tray) plus 30 sheets (standard Job Separator Tray)

PRINT FUNCTIONS

Controller language: PRESCRIBE II c Emulations: PCL6 (5c/XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and Open XPS Operating systems: All current Windows operating systems, MAC OS X Version 10.5 or higher, Unix, Linux as well as other

MAL US X Version 10.5 or rigner, Unix, Linux as well as other operating systems on request
Fonts/barcodes: 101 outline fonts (PCL 6, KPDL 3, Windows
Vista), 1 Bitmap font, 45 types of one-dimensional barcodes,
1 type of two-dimensional barcode (PDF417)

Print features: Encrypted PDF Direct Print, IPP printing,
e-mail printing, WSD print, secure printing via SSL, IPsec,
SNMPy3, quick copy, proof and hold, private print, job
storage and ioh management functionality.

storage and job management functionality

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google cloud print

COPY FUNCTIONS

Max. original size: A3/Ledger

Continuous copying: 1–999
Zoom range: 25–400% in 1% steps
Preset magnification ratios: 5 Reductions / 5 Enlargements

Exposure mode: Auto, manual: 7 steps Image adjustments: Text + Photo, Photo, Text, Map,

Printed document Features: Scan-once-copy-many, electronic sort, 2in1, 4in1,

job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change (PF-470 or PF-471 is required), copy density control, Prevent Bleed-Through, ID card copy, Skip blank page

Functionality: Scan-to-Email, Scan-to-FTP, Scan-to-SMB, Scan to USB Host, Network TWAIN, WIA , WSD scan Scan speed: 50 ipm (300 dpi, A4, b/w), 50 ipm (300 dpi, A4 colour)

Scan resolution: 600, 400, 300, 200 dpi (256 greyscales per colour) Max. scan size: A3, Ledger

Original recognition: Text, photo, text + photo, light text, optimised for OCR
File types: TIFF, PDF, A, JPEG, Open XPS, Encrypted

PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u Compression method: MMR/JPEG Features: Colour scan, integrated address book, Active

Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once, Blank page skip

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU -T Super G₃ Modem speed: Max. 33.6 kbps Transmission speed: Max. 33.6 kbps Scanning speed: 2.0 seconds or less Address book: 200 entries

Scanning density: Normal: 8 dot/mm x 3.85 line/mm (200 x 100 dpi) Fine: 8 dot/mm x 7.7 line/mm (200 x 200 dpi)
Superfine: 8 dot/mm x 15.4 line/mm (200 x 400 dpi)
Ultrafine: 16 dot/mm x 15.4 line/mm (400 x 400 dpi) Halftone: 256 grey scales

Maximum original size: A3, Ledger Compression method: IBIG, MMR, MR, MH Memory reception: 700 sheets or more Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19798 **TK-8115K Toner Kit**: Microfine toner black for 12,000 pages A4

Microfine toner cyan, magenta, yellow for 6,000 pages A4 Capacity of starter toner is black 3,000 pages, cyan, magenta, yellow 1,500 pages A4 **Staple:** SH-10, 5000 x 3 staples

OPTIONS

Fax System 13

Paper handling

PF-470 Paper feeder: Max. 500 sheets; 60–163 g/m²; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm) **PF-471 Paper feeder:** Max. 1,000 sheets; 60–163 g/m²; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm) DF-470* Paper feeder: Document finisher with AK-470, Max. 500 sheets A4; 60–163 g/m²; A3, A4, A5, B5, Letter, Legal, Custom (98 x 148 to 297 x 432 mm), positions stapling up to 50 sheets A4 or 25 sheets A3
*Bridge unit AK-470 is required for the use of DF-470
Security: Data security kit (E):

Memory upgrade: DDR3 1GB/2GB HD-6: SSD 32 GB for easy document management HD-7: SSD 128 GB for easy document management

SD card: for printing forms, fonts, logos, macro storage and for HyPASTM applications USB Flash Memory: Supports direct printing and scanning of PDF, XPS, TI FF, JPEG files via USB Host interface

UG-33: ThinPrint support
USB IC Card Reader + Card Authentication Kit (B): Support
for various authentication keys available. The card holder is standard

Optional interface

IB-36: Wireless LAN (802.11b/g/n) with Wi-Fi Direct IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/ 1,000 BaseT

IB-51: Wireless LAN Interface (802.11b/g/n)

18-31: wheless LAW interface (602:11D/g/ii) CB-470 Cabinet: Wooden desk with storage capacity, including castors (wheels) CB-472 Cabinet: Metal desk with storage capacity, including castors (wheels)

WARRANTY

1-year warranty as standard.** KYOCERA guarantees the drum and developer for 3 years or 300,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions



LIFE Up to 5-year on-site warranty extensions available for product and options.

















KYOCERA Document Solutions Europe B.V Bloemlaan 4 - 2132NP Hoofddorp - The Netherlands Tel +31 (0)20 6540 000 - Fax +31(0)20 653 1256 www.kvoceradocumentsolutions.eu - info@deu.kvocera.com

KYOCERA Document Solutions Inc. - 2-28, 1-Chome - Tamatsukuri Chuo-Ku – Osaka 540-8585 – Japan – www.kyoceradocumentsolutions.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. ecifications are subject to change without notice. Information is correct at time of going to press All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



^{**} Depending on the country